


**ANGULOS DESIGUALES. EN 573-3 / 755-9**

- Disponible
- Consultar
- Consultar

Dimensiones	Peso kg/m	Disponible AW6060 T66
-------------	-----------	-----------------------

Dimensiones	x	y	z	t	Peso kg/m	Disponible		
15	x	10	x	2,0	0,124	■		
20	x	10	x	1,5	0,115	○		
	x	10	x	2,0	0,151	■		
	x	15	x	2,0	0,178	■		
	x	15	x	3,0	0,259	■		
25	x	10	x	2,0	0,180	■		
	x	15	x	2,0	0,205	■		
	x	15	x	3,0	0,300	■		
	x	20	x	2,0	0,232	■		
30	x	10	x	2,0	0,209	■		
	x	15	x	2,0	0,232	■		
	x	15	x	3,0	0,340	■		
	x	20	x	2,0	0,259	■		
	x	20	x	3,0	0,381	■		
	x	20	x	4,0	0,497	■		
	x	25	x	3,0	0,421	■		
35	x	15	x	2,0	0,259	■		
	x	20	x	2,0	0,286	■		
	x	25	x	3,0	0,462	○		
40	x	10	x	2,0	0,259	■		
	x	15	x	2,0	0,286	■		
	x	20	x	1,5	0,237	+		
	x	20	x	2,0	0,313	■		
	x	20	x	3,0	0,462	■		
	x	20	x	4,0	0,600	■		
	x	25	x	2,0	0,340	■		
	x	25	x	3,0	0,502	■		
	x	30	x	2,0	0,367	■		
	x	30	x	3,0	0,540	■		
	x	30	x	4,0	0,710	■		
45	x	30	x	3,0	0,583	■		
50	x	15	x	2,0	0,340	■		
	x	20	x	2,0	0,367	■		
	x	20	x	3,0	0,540	■		
	x	25	x	2,0	0,394	■		
	x	25	x	3,0	0,580	■		
	x	25	x	4,0	0,767	■		
	x	25	x	5,0	0,945	+		
	x	30	x	2,0	0,421	■		



## ANGULOS DESIGUALES, EN 573-3 / 755-9

- Disponible
- Consultar
- Consultar

Dimensiones      Peso kg/m      Disponible AW6060 T66						
	x	30	x	3,0	0,620	■
	x	30	x	4,0	0,820	■
	x	30	x	5,0	1,013	■
	x	40	x	2,0	0,457	■
	x	40	x	3,0	0,705	■
	x	40	x	4,0	0,930	■
60	x	15	x	2,0	0,394	○
	x	20	x	2,0	0,421	■
	x	20	x	3,0	0,624	○
	x	25	x	2,5	0,557	○
	x	30	x	2,0	0,475	■
	x	30	x	3,0	0,705	■
	x	30	x	4,0	0,930	■
	x	30	x	5,0	1,148	■
	x	40	x	2,0	0,530	■
	x	40	x	3,0	0,790	■
	x	40	x	4,0	1,040	■
	x	40	x	5,0	1,282	■
70	x	20	x	2,0	0,475	■
	x	30	x	2,0	0,530	■
	x	30	x	3,0	0,786	■
	x	40	x	2,0	0,583	○
75	x	50	x	5,0	1,620	■
80	x	20	x	2,0	0,530	■
	x	30	x	3,0	0,870	■
	x	40	x	2,0	0,637	■
	x	40	x	3,0	0,950	■
	x	40	x	4,0	1,250	■
	x	40	x	5,0	1,553	■
	x	40	x	6,0	1,847	■
	x	50	x	3,0	1,029	■
	x	50	x	5,0	1,688	■
	x	60	x	4,0	1,469	■
	x	60	x	6,0	2,171	■
100	x	20	x	2,0	0,638	■
	x	30	x	2,0	0,691	○
	x	30	x	3,0	1,030	■
	x	40	x	3,0	1,110	■
	x	40	x	4,0	1,470	■



## ANGULOS DESIGUALES, EN 573-3 / 755-9

- Disponible
- Consultar
- Consultar

Dimensiones      Peso kg/m      Disponible AW6060 T66						
---	--	--	--	--	--	--

	x	50	x	3,0	1,190	■		
	x	50	x	5,0	1,960	■		
	x	50	x	6,0	2,333	■		
	x	50	x	8,0	3,067	■		
	x	50	x	10,0	3,780	■		
	x	60	x	6,0	2,495	■		
	x	60	x	8,0	3,283	○		
	x	80	x	6,0	2,819	■		
120	x	20	x	2,0	0,746	■		
	x	40	x	3,0	1,272	■		
	x	40	x	4,0	1,685	■		
	x	50	x	5,0	2,228	■		
	x	60	x	6,0	2,820	■		
	x	60	x	8,0	3,715	■		
	x	80	x	8,0	4,147	■		
	x	80	x	10,0	5,130	■		
130	x	30	x	3,0	1,272	■		
140	x	40	x	3,0	1,434	■		
150	x	50	x	4,0	2,117	■		
	x	50	x	5,0	2,630	■		
	x	50	x	8,0	4,140	■		
	x	75	x	8,0	4,690	■		
	x	100	x	5,0	3,308	■		
	x	100	x	10,0	6,480	■		
200	x	100	x	10,0	7,830	■		