


PERFIL-U, EN 573-3 / 755-9

- Disponible
- Consultar
- Consultar

		Dimensiones				Peso kg/m	AW6060 T66		
U 10	10	x	10	x	1,5	0,110	○		
		x	10	x	2,0	0,140	■		
		x	20	x	2,0	0,248	□		
U 12	12	x	12	x	2,0	0,173	■		
		U 15	15	x	15	x	1,5	0,170	○
x	15			x	2,0	0,221	■		
x	15			x	3,0	0,316	○		
U 18	18	x	20	x	2,0	0,275	■		
		x	18	x	2,0	0,270	○		
U 20	20	x	10	x	2,0	0,194	■		
		x	15	x	2,0	0,248	■		
		x	20	x	1,5	0,231	■		
		x	20	x	2,0	0,302	■		
		x	25	x	2,0	0,356	○		
		x	30	x	1,5	0,312	○		
U 23	23	x	30	x	2,0	0,410	■		
		x	40	x	2,0	0,518	■		
		x	23	x	1,5	0,267	■		
U 25	25	x	15	x	2,0	0,275	□		
		x	20	x	2,0	0,329	■		
		x	20	x	3,0	0,478	○		
		x	25	x	2,0	0,383	■		
		x	25	x	3,0	0,560	■		
		x	35	x	2,0	0,491	○		
U 30	30	x	40	x	2,0	0,545	○		
		x	15	x	2,0	0,302	■		
		x	15	x	3,0	0,437	○		
		x	20	x	2,0	0,356	■		
		x	20	x	3,0	0,520	■		
		x	30	x	2,0	0,464	■		
U 35	35	x	30	x	3,0	0,680	■		
		x	40	x	3,0	0,842	■		
		x	50	x	3,0	1,004	■		
		x	20	x	2,0	0,383	■		
		x	25	x	2,0	0,438	○		
		x	35	x	2,0	0,545	■		
U 40	40	x	35	x	3,0	0,802	■		
		x	15	x	2,0	0,356	○		
		x	20	x	2,0	0,410	■		


PERFIL-U, EN 573-3 / 755-9

- Disponible
- Consultar
- Consultar

		Dimensiones				Peso kg/m	AW6060 T66		
		x	20	x	2,5	0,506	■		
		x	20	x	3,0	0,600	■		
		x	25	x	3,0	0,680	○		
		x	30	x	3,0	0,761	■		
		x	30	x	4,0	0,994	■		
		x	40	x	2,0	0,627	■		
		x	40	x	3,0	0,923	■		
		x	40	x	4,0	1,210	■		
U 45	45	x	20	x	2,0	0,437	○		
U 50	50	x	20	x	2,0	0,464	■		
		x	25	x	2,0	0,518	■		
		x	30	x	2,0	0,572	■		
		x	30	x	3,0	0,842	■		
		x	30	x	4,0	1,102	■		
		x	40	x	4,0	1,318	■		
		x	50	x	3,0	1,167	■		
		x	50	x	4,0	1,535	■		
		x	50	x	5,0	1,890	■		
U 55	55	x	25	x	2,0	0,545	○		
U 60	60	x	20	x	2,0	0,518	■		
		x	30	x	3,0	0,924	■		
		x	30	x	4,0	1,210	○		
		x	40	x	2,5	0,911	■		
		x	40	x	3,0	1,085	■		
		x	40	x	4,0	1,428	■		
		x	40	x	5,0	1,756	■		
		x	60	x	3,0	1,409	■		
		x	60	x	4,0	1,858	■		
		x	60	x	5,0	2,295	■		
U 65	65	x	55	x	2,5	1,148	■		
U 80	80	x	20	x	2,0	0,626	■		
		x	30	x	3,0	1,085	■		
		x	40	x	3,0	1,247	■		
		x	40	x	4,0	1,642	■		
		x	40	x	5,0	2,025	■		
		x	50	x	5,0	2,297	■		
		x	80	x	4,0	2,506	■		
U 86	86	x	40	x	3,0	1,296	■		
U 90	90	x	50	x	3,0	1,490	■		


PERFIL-U, EN 573-3 / 755-9

- Disponible
- Consultar
- Consultar

Dimensiones Peso kg/m AW6060 T66									
U 100	100	x	20	x	2,0	0,734	■		
		x	40	x	3,0	1,410	■		
		x	50	x	3,0	1,571	■		
U 120	120	x	50	x	5,0	2,570	■		
		x	40	x	3,0	1,571	■		
U 125	125	x	63	x	6,0	3,872	■		
		x	80	x	8,0	5,810	○		
U 140	140	x	60	x	7,0	4,650	■		
		x	70	x	8,0	5,702	■		
U 160	160	x	80	x	8,0	6,566	■		
		x	80	x	10,0	8,100	■		
U 200	200	x	100	x	10,0	10,260	○		