



TUBO RECTANGULAR, EN 573-3 / 755-8

- Disponible
- Consultar
- Consultar

Dimensiones					Peso kg/m	Disponible AW6060 T66				
20	x	10	x	1,5	0,219			■		
	x	10	x	2,0	0,286			■		
25	x	15	x	2,0	0,335			■		
	x	15	x	1,5	0,300			○		
	x	15	x	2,0	0,389			■		
30	x	20	x	2,0	0,442			■		
	x	10	x	1,5	0,300			○		
	x	10	x	2,0	0,389			■		
	x	15	x	1,5	0,340			■		
	x	15	x	2,0	0,443			■		
	x	20	x	1,5	0,381			■		
	x	20	x	2,0	0,497			■		
	x	20	x	3,0	0,713			■		
35	x	25	x	2,0	0,551			■		
	x	20	x	2,0	0,551			■		
	x	25	x	2,0	0,605			■		
40	x	10	x	2,0	0,498			■		
	x	15	x	2,0	0,551			■		
	x	20	x	1,5	0,462			■		
	x	20	x	2,0	0,605			■		
	x	20	x	3,0	0,875			■		
	x	20	x	4,0	1,123			■		
	x	25	x	2,0	0,659			■		
45	x	30	x	2,0	0,710			■		
	x	30	x	3,0	1,037			■		
	x	30	x	4,0	1,339			■		
	x	20	x	2,0	0,659			■		
50	x	25	x	2,0	0,713			■		
	x	15	x	2,0	0,659			■		
	x	20	x	2,0	0,713			■		
	x	20	x	3,0	1,030			■		
	x	20	x	4,0	1,339			■		
	x	25	x	2,0	0,770			■		
	x	25	x	3,0	1,118			■		
	x	30	x	2,0	0,821			■		
50	x	30	x	2,5	1,013			□		
	x	30	x	3,0	1,200			■		
	x	40	x	2,0	0,930			■		
	x	40	x	3,0	1,361			■		



TUBO RECTANGULAR, EN 573-3 / 755-8

- Disponible
- Consultar
- Consultar

Dimensiones					Peso kg/m	Disponible AW6060 T66			
60	x	40	x	4,0	1,777		■		
	x	20	x	2,0	0,821		■		
	x	20	x	3,0	1,200		■		
	x	20	x	4,0	1,555		■		
	x	25	x	2,0	0,875		■		
	x	25	x	3,0	1,280		■		
	x	30	x	2,0	0,930		■		
	x	30	x	3,0	1,361		■		
	x	30	x	4,0	1,771		○		
	x	40	x	2,0	1,037		■		
	x	40	x	2,5	1,283		■		
	x	40	x	3,0	1,523		■		
	x	40	x	4,0	1,990		■		
	x	40	x	5,0	2,430		○		
70	x	50	x	3,0	1,685		■		
	x	50	x	4,0	2,203		■		
	x	20	x	2,0	0,929		■		
	x	30	x	3,0	1,523		■		
	x	40	x	3,0	1,685		■		
80	x	50	x	4,0	2,419		■		
	x	20	x	2,0	1,037		■		
	x	30	x	2,0	1,145		■		
	x	30	x	3,0	1,684		■		
	x	40	x	2,0	1,253		■		
	x	40	x	3,0	1,847		■		
	x	40	x	4,0	2,419		■		
	x	50	x	2,0	1,360		■		
	x	50	x	3,0	2,009		■		
	x	50	x	4,0	2,635		■		
	x	60	x	3,0	2,171		■		
100	x	60	x	4,0	2,851		■		
	x	18	x	2,0	1,231		■		
	x	20	x	2,0	1,253		■		
	x	25	x	2,0	1,307		■		
	x	30	x	2,0	1,360		■		
	x	30	x	3,0	2,010		■		
	x	40	x	2,0	1,469		■		
	x	40	x	3,0	2,171		■		
	x	40	x	4,0	2,850		■		



TUBO RECTANGULAR, EN 573-3 / 755-8

■ Disponible

○ Consultar

□ Consultar

Dimensiones					Peso kg/m	Disponible AW6060 T66			
	x	50	x	2,0	1,577		■		
	x	50	x	3,0	2,333		■		
	x	50	x	4,0	3,067		■		
	x	50	x	5,0	3,780		■		
	x	60	x	2,0	1,685		■		
	x	60	x	3,0	2,495		■		
	x	60	x	4,0	3,283		■		
	x	60	x	5,0	4,050		■		
	x	80	x	3,0	2,819		■		
120	x	20	x	2,0	1,470		■		
	x	30	x	2,0	1,577		■		
	x	30	x	3,0	2,333		■		
	x	40	x	2,0	1,685		■		
	x	40	x	4,0	3,283		■		
	x	50	x	3,0	2,657		■		
	x	50	x	4,0	3,497		■		
	x	60	x	3,0	2,820		■		
	x	60	x	4,0	3,715		■		
	x	60	x	5,0	4,590		○		
	x	80	x	3,0	3,142		■		
	x	80	x	4,0	4,147		■		
140	x	18	x	2,0	1,663		■		
	x	20	x	3,0	2,495		■		
	x	40	x	3,0	2,819		○		
	x	40	x	4,0	3,715		■		
	x	60	x	4,0	4,147		■		
	x	80	x	4,0	4,577		■		
150	x	18	x	2,0	1,771		■		
	x	40	x	4,0	3,931		■		
	x	50	x	2,0	2,117		■		
	x	50	x	3,0	3,140		■		
	x	50	x	4,0	4,150		■		
	x	50	x	5,0	5,130		■		
	x	60	x	3,0	3,305		○		
	x	80	x	4,0	4,800		■		
	x	100	x	3,0	3,953		■		
	x	100	x	4,0	5,227		■		
160	x	40	x	4,0	4,147		■		
	x	80	x	4,0	5,010		■		



TUBO RECTANGULAR. EN 573-3 / 755-8

- Disponible
- Consultar
- Consultar

Dimensiones					Peso kg/m	Disponible AW6060 T66				
180	x	40	x	4,0	4,579			■		
	x	50	x	4,0	4,795			■		
	x	60	x	3,0	3,791			■		
	x	60	x	4,0	5,011			■		
200	x	18	x	2,0	2,311			■		
	x	20	x	2,0	2,333			■		
	x	40	x	3,0	3,791			■		
	x	50	x	4,0	5,300			■		
	x	80	x	4,0	5,875			■		
	x	100	x	3,0	4,763			○		
	x	100	x	4,0	6,307			■		
	x	150	x	4,0	7,387			○		
206	x	30	x	3,0	3,726			○		
250	x	50	x	3,0	4,763			■		
	x	50	x	4,0	6,307			○		
	x	100	x	4,0	7,387			□		
	x	150	x	4,0	8,467			○		
300	x	50	x	4,0	7,387			○		
	x	100	x	3,0	6,383			□		