


**TUBO REDONDO, EXTRUIDO EN 573-3 / 755-8**

- Disponible
- Consultar
- Consultar

Dimensiones		Peso kg/m	Disponible AW6060 T66	
5	x	1,0	0,034	□
6	x	1,0	0,042	□
8	x	1,0	0,059	■
10	x	1,0	0,076	■
	x	2,0	0,136	■
12	x	1,0	0,093	■
	x	1,5	0,134	□
	x	2,0	0,170	■
13	x	1,0	0,102	□
	x	1,5	0,146	□
14	x	1,0	0,110	■
	x	1,5	0,159	○
	x	2,0	0,203	■
	x	2,5	0,286	○
15	x	1,0	0,119	■
	x	1,5	0,172	■
	x	2,0	0,225	■
16	x	1,0	0,127	○
	x	1,5	0,184	■
	x	2,0	0,237	■
	x	2,5	0,286	○
18	x	1,5	0,210	■
	x	2,0	0,271	■
19	x	1,5	0,223	□
20	x	1,0	0,161	■
	x	1,5	0,235	■
	x	2,0	0,305	■
	x	3,0	0,432	■
	x	4,0	0,542	■
22	x	5,0	0,636	■
	x	1,0	0,178	■
	x	1,5	0,261	■
	x	2,0	0,339	■
	x	2,5	0,477	■
25	x	1,0	0,203	○
	x	1,5	0,300	■
	x	2,0	0,390	■
	x	3,0	0,560	■
	x	5,0	0,848	■
28	x	1,5	0,337	■
	x	2,0	0,441	■


**TUBO REDONDO, EXTRUIDO EN 573-3 / 755-8**

- Disponible
- Consultar
- Consultar

Dimensiones      Peso kg/m      Disponible AW6060 T66						
30	x	3,0	0,636	○		
	x	1,5	0,369	■		
	x	2,0	0,475	■		
	x	2,5	0,583	■		
	x	3,0	0,687	■		
	x	4,0	0,881	■		
32	x	5,0	1,060	■		
	x	1,5	0,387	□		
	x	2,0	0,509	■		
35	x	3,0	0,738	■		
	x	1,5	0,426	■		
	x	2,0	0,560	■		
	x	2,5	0,689	■		
	x	3,0	0,814	■		
38	x	4,0	1,051	■		
	x	5,0	1,270	■		
	x	2,0	0,610	■		
	x	3,0	0,890	○		
	x	4,0	1,153	■		
40	x	1,5	0,490	■		
	x	2,0	0,644	■		
	x	2,5	0,795	■		
	x	3,0	0,940	■		
	x	4,0	1,220	■		
	x	5,0	1,484	■		
	x	10,0	2,544	■		
42	x	2,0	0,678	○		
	x	3,0	0,990	■		
	x	4,0	1,289	○		
45	x	1,5	0,553	■		
	x	2,0	0,730	■		
	x	2,5	0,901	○		
	x	3,0	1,070	■		
48	x	5,0	1,700	■		
	x	1,5	0,591	○		
	x	2,0	0,780	■		
	x	2,5	0,965	■		
	x	3,0	1,140	■		
50	x	4,0	1,490	■		
	x	1,0	0,415	○		


**TUBO REDONDO, EXTRUIDO EN 573-3 / 755-8**

- Disponible
- Consultar
- Consultar

Dimensiones		Peso kg/m	Disponible AW6060 T66
	x 1,5	0,617	■
	x 2,0	0,814	■
	x 2,5	1,010	■
	x 3,0	1,195	■
	x 4,0	1,560	■
	x 5,0	1,910	■
	x 10,0	3,393	■
55	x 2,0	0,899	■
	x 2,5	1,113	■
	x 5,0	2,120	■
60	x 1,5	0,744	■
	x 2,0	0,983	■
	x 2,5	1,220	■
	x 3,0	1,450	■
	x 4,0	1,899	■
	x 5,0	2,330	■
	x 10,0	4,240	■
	x 15,0	5,723	○
65	x 2,0	1,070	■
	x 5,0	2,543	■
70	x 2,0	1,153	■
	x 2,5	1,537	○
	x 3,0	1,704	■
	x 4,0	2,238	■
	x 5,0	2,755	■
	x 10,0	5,087	■
75	x 2,5	1,537	■
	x 5,0	2,967	■
76	x 3,0	1,857	■
80	x 2,0	1,323	■
	x 2,5	1,643	■
	x 3,0	1,958	■
	x 4,0	2,580	■
	x 5,0	3,180	■
	x 10,0	5,934	■
90	x 2,0	1,492	○
	x 3,0	2,213	■
	x 4,0	2,916	○
	x 5,0	3,603	■
	x 10,0	6,782	■


**TUBO REDONDO, EXTRUIDO EN 573-3 / 755-8**

- Disponible
- Consultar
- Consultar

Dimensiones      Peso kg/m      Disponibilidad AW6060 T66						
100	x	2,0	1,662	■		
	x	3,0	2,467	■		
	x	4,0	3,256	■		
	x	5,0	4,027	■		
	x	10,0	7,630	■		
108	x	3,0	2,671	■		
110	x	1,5	1,380	○		
	x	3,0	2,721	■		
	x	5,0	4,451	■		
120	x	3,0	2,977	■		
	x	4,0	3,934	○		
	x	5,0	4,875	■		
	x	10,0	9,326	○		
125	x	4,0	4,103	■		
130	x	5,0	5,299	■		
140	x	4,0	4,612	○		
	x	5,0	5,723	■		
	x	10,0	11,021	○		
150	x	3,0	3,740	■		
	x	5,0	6,150	■		
	x	10,0	11,869	■		
160	x	5,0	6,570	■		
180	x	5,0	7,418	■		
200	x	5,0	8,270	■		
230	x	5,0	9,538	○		
250	x	5,0	10,386	■		